



100% True DIY

Ornato Loose Lay contains a 0.5 mm fiberglass layer which ensures the plank will not be affected by normal fluctuating temperatures in the environment. For this reason, we recommend for the best result Ornato Loose lay be laid with no gaps between any plank or perimeter surface. Loose Lay tiles and planks can be installed without adhesive and commercial areas, including bedroom, kitchen, laundry etc.

Specifications

Tile Size (mm)	EN 427	177.8 X 1219.2
Total Thickness (mm)	EN 649	5.0 mm
Wear Layer Thickness (mm)	EN 428	0.5 [\pm 0.05]
Peeling strength of Layer	EN 431	Pass
Weight per Ct	EN 430	18.7 kg/Box
Packing	EN 427	10 Planks/Box
Impact sound reduction	ISO 10140	L'nT,w + CI 59
Dimension stability	EN 434	Pass
Colour Fastness to light	ISO 105 B02	\geq Grade 6
Static indentation	EN 433	\leq 0.1 mm
Flexibility	EN 435	Pass
Abrasion resistance	EN 660-2	Class T
Castor chair resistance	EN 425	Pass
Slip resistance	EN 13893	>0.3
	DIN 51130 [Australia]	R10 [HIGH*]
Fire Rating	EN 13501 -1	Bfl – S1
	ASTM E 84	Class 1
Usage category	EN 685	23/42
Resistance to chemical	EN 423	Pass
Electrostatic Properties	EN 1815	< 2 kv
Surface Treatment		PUR
Embossing	Regular/Deep	
The above information is subject to modifications for the benefit of further improvements		

LOOSE LAY [Non-Slip] – CARGO INFORMATION

Thickness [mm]	Wearlayer [mm]	Width & Length [mm]	Per CTN	20 FT Container loading Quantity
5.0	0.5	177.8 X 1219.2	10 pcs [2.167 sqm]	2,167 sqm [1,000 CTN]

